

EMERGENCY ESCAPE LIGHTING

EXIT M

Materials

Body	White , grey or black polycarbonate body
Cover	Transperent polycarbonate

Power Supply

Self contained	220-240VAC/50-60HZ
Central battery	220-240VAC /50-60Hz ; 176-275VDC
Central battery	FZLV-24VDC

Autonomy and Batteries

Basic	1h or 3h, Ni-cd 3.6v batteries
Standard	1h or 3h, Ni-cd 3.6v batteries
Premium	1h or 3h, LiFePo ₄ 6.4V batteries

Options

SE	Non maintained
SA	Maintained
PT	Manual test button
AT	autotest
RU	Rubic UNA central monitoring
RW	Rubic UNA wireless central monitoring
FZLV	Central battery FZLV 24VDC
CB	Central battery

Light source

LED	1w, 2w, 3w
------------	------------

Mounting

surface	Wall , ceiling
Optionaly recessed	Wall , ceiling
Optionaly Pendant	ceiling

Charging

Basic	Max. 24h
Standard	Max. 24h
Premium	Max. 12h ; energy-saving electronic charger

Ambient temera- ture

0° - 40°

IP Rating

IP65

Insulation Class

II or III

Dimensions(mm)

276x143x44

Recessing Cut (mm)

125x260

Additional information

LED indicator signalizes mains powers supply and battery charging


Deep discharge protection

Optional adaptation of the fixture for low temperatures up to -25° c

III class of insulation of FZLV version




DIMENSIONS (mm):



RECESSING CUT (mm):

• wall

• ceiling



220-240V AC 50-60Hz	176-275V DC	24V DC	LED	IP65	Recessed
LiFePO ₄	Ni-Cd	Autotest	Manual test	III	CE
Deep discharge protection	Low temp	12			

SELF-CONTAINED CONFIGURATION

CODE	POWER	MODULE	AUTONOMY [h]	MODE	OPTIONS	COLOR
BASIC						
ETE	1W	E	1 3	SE	PT X	WH GR BL
STANDARD						
ETE	1W	C	1 3	SA	PT X	WH GR BL
	2W	C	1 3	SA	PT X	WH GR BL
	3W	C	1 3	SA	PT X	WH GR BL
PREMIUM						
ETE	1W	B	1 3	SA	AT RU RW	WH GR BL
	2W	B	1 3	SA	AT RU RW	WH GR BL
	3W	B	1 3	SA	AT RU RW	WH GR BL

OUTPUT IN EMERGENCY MODE

POWER	OUTPUT [lm]
BASIC	
1W	130
STANDARD	
1W	130
2W	250
3W	320
PREMIUM	
1W	135
2W	270
3W	350

CENTRAL BATTERY CONFIGURATION - NON-ADDRESSABLE

CODE	POWER	MODULE	SYSTEM	OPTIONS	COLOR
ETE	1W	F	CB	CBS X	WH GR BL
	2W	F	CB	CBS X	WH GR BL
	3W	F	CB	CBS X	WH GR BL

OUTPUT IN EMERGENCY MODE

POWER	OUTPUT [lm]
1W	130
2W	270
3W	350

CENTRAL BATTERY CONFIGURATION - ADDRESSABLE

CODE	POWER	MODULE	SYSTEM	OPTIONS	COLOR
ETE	1W	Z	CB	ADE ADP	WH GR BL
	2W	Z	CB	ADE ADP	WH GR BL
	3W	Z	CB	ADE ADP	WH GR BL

OUTPUT IN EMERGENCY MODE

POWER	OUTPUT [lm]
1W	130
2W	270
3W	350

FZLV SYSTEM CONFIGURATION

CODE	POWER	SYSTEM	COLOR
ETE	1W	FZLV	WH GR BL
	2W	FZLV	WH GR BL
	3W	FZLV	WH GR BL

OUTPUT IN EMERGENCY MODE

POWER	OUTPUT [lm]
1W	130
2W	270
3W	350

LEGEND:

- ETE - fitting EXIT M
- E - electronic gear for BASIC self-contained fittings
- C - electronic gear for STANDARD self-contained fittings
- B - electronic gear for PREMIUM self-contained fittings
- F - electronic gear for central battery fittings
- Z - electronic gear for addressable central battery fittings
- SE - non-maintained
- SA - maintained (with an option of connecting as non-maintained)
- PT - manual test button
- X - fitting without additional options
- AT - autotest
- RU - RUBIC UNA central monitoring system
- RW - RUBIC UNA Wireless central monitoring
- CB - central battery version
- CBS - central battery for circuit monitoring
- ADE - central battery with ADE address module
- ADP - central battery with ADP address module - SMART technology
- FZLV - central battery FZLV 24 VDC
- WH - white color
- GR - grey color
- BL - black color

