

EXIT L DS



AC
220-240V
50-60Hz

DC
176-275V

DC
48V

LED

IP65

IK08



d=30m



Ni-Cd

LiFePO₄



MATERIALS

White, grey or black polycarbonate body • Transparent or opal polycarbonate cover

MOUNTING

Surface • Optionally pendant⁽²⁾ • Optionally wall or ceiling bracket ⁽³⁾

POWER SUPPLY

Self contained – 220 - 240VAC/50 - 60Hz
Central battery – 220 - 240VAC/50 - 60Hz; 176 - 275VDC
Central battery FZLV II – 48VDC
Central battery FZLV – 24VDC

LIGHT SOURCE

2W, 3W LED
Colour temperature: 6000K
Lifetime: 50000h

CHARGING

Standard: max. 24h
Premium: max. 12h; energy-saving electronic charger

AUTONOMY AND BATTERIES

Standard: 1h or 3h, Ni-Cd 3,6V batteries
Premium: 1h or 3h, LiFePO₄ 6,4V batteries

INSULATION CLASS

II or III

IP & IK RATING

IP65, IK08

VIEWING DISTANCE

30 m

VIEWING METHOD

Double-sided ⁽³⁾

AMBIENT TEMPERATURE

Self-contained: t_a: 0°C ÷ 40°C • t_a: -25°C ÷ 40°C – together with heater for low temperatures
Central battery: t_a: -25°C ÷ 50°C



OPTIONS

SE – non maintained • SA – maintained • AT – autotest • PT – manual test button
• RU – Rubic UNA central monitoring • RW – Rubic UNA Wireless central monitoring
• FZLV2 – central battery FZLV II 48VDC • CB – central battery

ADDITIONAL INFORMATION

LED indicator signalizes mains power supply and battery charge • Deep discharge protection
• Optional adaptation of the fixture for low temperatures up to -25°C with HTR 25 • III class of insulation of FZLV and FZLV2 version • ⁽¹⁾ see accessory for recessed mounting • ⁽²⁾ see accessory for pendant mounting • ⁽³⁾ see accessory bracket • ⁽⁴⁾ select 2pc of pictogram number from datasheet Pictograms.

DIMENSIONS [mm]



⁽⁴⁾ pictogram

SELF-CONTAINED CONFIGURATION

	CODE	POWER	MODULE	AUTONOMY [h]		MODE		OPTIONS			COLOR			COVER		
				1	3	SE	SA	PT	AT	X	WH	GR	BL	TR	OP	
STANDARD	ETLD	2W	E C	1	3	SE	SA	PT	AT	X	WH	GR	BL	TR	OP	
		3W	E C	1	3	SE	SA	PT	AT	X	WH	GR	BL	TR	OP	
PREMIUM	ETLD	2W	B	1	3	SE	SA	AT	RU	RW	RD	WH	GR	BL	TR	OP
		3W	B	1	3	SE	SA	AT	RU	RW	RD	WH	GR	BL	TR	OP

CENTRAL BATTERY CONFIGURATION - NON-ADDRESSABLE

CODE	POWER	MODULE	SYSTEM	OPTIONS		COLOR		
ETLD	2W	F	CB	CBS	X	WH	GR	BL
	3W	F	CB	CBS	X	WH	GR	BL

CENTRAL BATTERY CONFIGURATION – ADDRESSABLE

CODE	POWER	MODULE	SYSTEM	OPTIONS	COLOR		
ETLD	2W	Z	CB	ADE	WH	GR	BL
	3W	Z	CB	ADE	WH	GR	BL

FZLV SYSTEM CONFIGURATION

CODE	POWER	SYSTEM	COLOR		
ETLD	2W	FZLV2	WH	GR	BL
	3W	FZLV2	WH	GR	BL

LEGEND:

ETLD	fixture EXIT L DS
C	electronic gear for STANDARD self-contained fittings
B	electronic gear for PREMIUM self-contained fittings
F	electronic gear for central battery fittings
Z	electronic gear for addressable central battery fittings
SE	non maintained
SA	maintained
PT	manual test button
X	fitting without additional options
AT	autotest
RU	Rubic UNA central monitoring
RW	Rubic UNA Wireless central monitoring
RD	DALI central monitoring
FZLV2	central battery FZLV II 48 VDC
CB	central battery version
CBS	central battery for circuit monitoring
ADE	address module for CBS 2.0 – SMART technology
WH	white color
GR	grey color
BL	black color
TR	transparent polycarbonate cover
OP	opal polycarbonate cover

