

# ESCAPE ALU AW



AC  
220-240V  
50-60Hz

DC  
176-275V

DC  
24V

DC  
48V

LED

IP20

IK08



d=30m



CE



LiFePO<sub>4</sub>

## MATERIALS

White, black or silver aluminium body • Plexi glass

## MOUNTING

Surface

## POWER SUPPLY

Self contained – 220 - 240VAC/50 - 60Hz  
Central battery – 220 - 240VAC/50 - 60Hz; 176 - 275VDC  
Central battery FZLV II – 48VDC  
Central battery FZLV – 24VDC

## LIGHT SOURCE

2W LED  
**Colour temperature:** 6000K  
**Lifetime:** 50000h

## CHARGING

max. 12h; energy-saving electronic charger

## AUTONOMY AND BATTERIES

1h or 3h, LiFePO<sub>4</sub> 3,2V batteries

## INSULATION CLASS

II or III

## IP & IK RATING

IP20, IK08

## VIEWING DISTANCE

30 m

## VIEWING METHOD

Double-sided

## AMBIENT TEMPERATURE

**Self-contained:** t<sub>g</sub>: 0°C ÷ 40°C **Central battery:** t<sub>g</sub>: 0°C ÷ 50°C


## OPTIONS

SE – non maintained • SA – maintained • PT – manual test button • AT – autotest • RU – Rubic UNA central monitoring • FZLV – central battery FZLV 24VDC • FZLV2 – central battery FZLV II 48VDC • CB – central battery

## ADDITIONAL INFORMATION

LED indicator signalizes mains power supply and battery charge • Deep discharge protection  
• III class of insulation of FZLV and FZLV2 versions • <sup>(1)</sup> see accessory for recessed mounting  
• <sup>(2)</sup> select 2pc of pictogram number from datasheet Pictograms

## DIMENSIONS [mm]



<sup>(2)</sup> pictogram

**SELF-CONTAINED CONFIGURATION**

| PREMIUM | CODE | POWER | MODULE | AUTONOMY [h] |   | MODE |    | OPTIONS |    |    |    | COLOR |    |    | PICTOGRAM |
|---------|------|-------|--------|--------------|---|------|----|---------|----|----|----|-------|----|----|-----------|
|         | ESAW | 2W    | B      | 1            | 3 | SE   | SA | X       | PT | AT | RU | WH    | SR | BL | XXYY      |

**CENTRAL BATTERY CONFIGURATION – ADDRESSABLE**

| CODE | POWER | MODULE | SYSTEM | OPTIONS |     | COLOR |    |    | PICTOGRAM |
|------|-------|--------|--------|---------|-----|-------|----|----|-----------|
| ESAW | 2W    | Z      | CB     | ADE     | ADP | WH    | SR | BL | XXYY      |

**FZLV SYSTEM CONFIGURATION**

| CODE | POWER | SYSTEM |      | COLOR |    |    | PICTOGRAM |
|------|-------|--------|------|-------|----|----|-----------|
| ESAW | 2W    | FZLV2  | FZLV | WH    | SR | BL | XXYY      |

**LEGEND:**

|      |  |       |   |
|------|--|-------|---|
| ESAW | fixture ESCAPE ALU AW                                    | ADE   | address module for CBS 2.0 – SMART technology |
| B    | electronic gear for PREMIUM self-contained fittings      | ADP   | address module for CBS 1.0 – SMART technology |
| Z    | electronic gear for addressable central battery fittings | FZLV2 | central battery FZLV II 48 VDC                |
| SE   | non-maintained   | FZLV  | central battery FZLV 24VDC                    |
| SA   | maintained   | WH    | white color                                   |
| PT   | manual test button                                       | SR    | silver color                                  |
| X    | fitting without additional options                       | BL    | black color                                   |
| AT   | autotest   | XX    | pictogram from the front side ID (e.g. 21)    |
| RU   | Rubic UNA central monitoring                             | YY    | pictogram on the back side ID (e.g. 22)       |
| CB   | central battery version                                  |       |   |

